

Model: FH4525Y-XC3A

Product Description

Type:	Reciprocating Compressors
Application:	HBP - High Back Pressure
ProductDescription:	R-134a/R-513A
Voltage/Frequency:	220-240V ~ 50Hz
Version:	N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					

General

Evaporating Temp. Range:	-15°C to 15°C (5°F to 59°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	0
Weight Unit of Measure:	
Displacement (cc):	63
Oil Type:	Polyolester
Viscosity (cSt):	32
Oil Charge (cc):	1140

Electrical

Voltage Range (50 Hz):	198-264
Voltage Range (60 Hz):	
Locked Rotor Amps (LRA):	52
Rated Load Amps (RLA 50 Hz):	9.5
Rated Load Amps (RLA 60 Hz):	0
Max. Continuous Current (MCC in Amps):	14
Motor Resistance (Ohm) - Main:	1.31
Motor Resistance (Ohm) - Start:	3.8
Motor Type:	CSR
Overload Type:	
Relay Type:	

Agency Approval

CE Listed