

**Model: AE2425Z-AA3C (AE2425Z-AA)**
**Product Description**

**Type:** Reciprocating  
**Application:** LBP - Low Back Pressure  
**Refrigerant:** R-404A  
**Voltage/Frequency:** 115V ~ 60Hz  
**Version:** N/A


**Product Specifications**
**Performance**

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	115V ~ 60HZ	2650	668	777	588	4.51	1.14	1.32	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)	32°C (90°F)

**General**

**Evaporating Temp. Range:** N/A  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

**Mechanical**

**Weight:** 0  
**Weight Unit of Measure:** N/A  
**Displacement (cc):** 12.01  
**Oil Type:** Polyolester  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 386.65

**Electrical**

**Voltage Range (50 Hz):** N/A  
**Voltage Range (60 Hz):** 103-127  
**Locked Rotor Amps (LRA):** 39  
**Rated Load Amps (RLA 50 Hz):** 0  
**Rated Load Amps (RLA 60 Hz):** 5.87  
**Max. Continuous Current (MCC in Amps):** 0  
**Motor Resistance (Ohm) - Main:** .94  
**Motor Resistance (Ohm) - Start:** 3.89  
**Motor Type:** CSR  
**Overload Type:** N/A  
**Relay Type:** N/A

**Agency Approval**

cURus Recognized